

Road Work Proposal #1, #2, #3 Town of Adams, Adams County

Type of work: Chip and Seal as described below

10th Ave., 11th Ave, 9th Ave. ROAD WORK PROPOSAL #1. #2. #3 Each project shall receive an individual bid price

TYPE OF WORK: BAR SEAL AND FA-2 CHIP SEAL On, **Location #1--10th Ave starting 10ft. south of the railroad tracks to the culvert for Duck Creek-- #2 11th Ave From Dover Dr. south to Duck Creek Dr.--#3 9th Ave, from Deerborn Ave. north to County Road "J"**
This proposal, submitted by the undersigned bidder to the Town of Adams, is in accordance with the advertised request for proposals. The bidder is to furnish and deliver all materials, and to perform all work for the improvement of the designated project in the time specified, in accordance with the appended Proposal Requirements and Conditions.

Bids are due on, or before: Monday March 9th, 2026 at 11:00 AM. All bids need to presented in a sealed envelope to the Town of Adams Highway Crew Director Dick Buhalog at the Town hall. The envelop shall have the project number listed on the front of the envelop and addressed to; "The Town of Adams Chair. Each project shall be placed in a separate sealed envelope

Proposal guaranty required, \$_____ (attach proposal guaranty or bid bonding equal to 5% of bid). Payable to:
Town of Adams, Adams County
P.O. Box 801
1980 11th Ave
Friendship, Wi. 53934

All bids for public works projects shall be accompanied by a certified check or a bid bond equal to at least 5% of the bid, payable to the Town of Adams, as a guarantee that if the bid is accepted the bidder will execute and file the proper contract and bond within the time established by the Town. If the successful bidder files the contract and bond, upon the execution of the contract by the Town, the check shall be returned. In the event the successful bidder fails to file such contract and bond, the amount of the check or bid bond shall be forfeited to the Town as liquidated damages.

This certifies that the undersigned bidder, duly sworn, is an authorized representative of the firm named above; that the bidder has examined and carefully prepared the bid from the plans/ specifications and checked the same in detail before submitting this proposal or bid. The bidder or agents, officer, or employees certify that they have not, either directly or indirectly, entered into any agreement, participated in any collection, or otherwise taken any action in restraint of free competitive bidding in connection with this proposal or bid.

Subscribed and sworn to before me this date: _____

Signature, Notary Public

Bidder Signature

Print Name, Notary Public

Print Bidder Name

Date Commission Expires

Bidder Title

BAR SEAL AND FA-2 CHIP SEAL

1. Scope of work: This work shall consist of furnishing all materials, equipment, and labor necessary for the application of Bituminous Seal Coating as directed. Bar seal consists of a full width chip seal on the existing Blacktop surface.

Project Location: Site #1--10th Ave 10 ft. south of the railroad tracks to the culvert for Duck Creek— Site #2-- 11th Ave from Dover Dr. south to Duck Creek Dr.— Site #3-- 9th Ave, from Deerborn Ave. north to County Road “J”

Completion date shall be Oct 1, 2026. A penalty shall be imposed of \$500.00 for each day beyond completion date that the project is not completed. The contractor may apply to the Town Board for a waiver of such penalty if the delay was the result of unexpected, extraordinary weather conditions, or other conditions that were out of the contractor’s control.

2. Description: The Work shall consist of bituminous seal coating with stone cover aggregate. The work shall be done in accordance with Section 475, 2014 Edition, State of Wisconsin Department of Transportation “standard Specifications for Highway and Structure Construction quote”.

3. Materials: Materials furnished and used in the work shall conform to the requirements of Section 475.3. And document of bill of lading of Hardrock Chip. Bituminous Material: The bituminous material to be furnished and applied shall be CRS-2P (Polymer-modified) emulsion. The emulsion shall be applied at a rate of 0.30 +/- .03 gallons per square yard. The bitumen shall be applied at the appropriate temperature for the particular grade. Cover Aggregate: The cover aggregate shall meet the requirements of the sieve specifications, and conform to the following sieve size:

Sieve Size Percent Passing

½ inch 100%

3/8 inch 100%

¼ inch 100%

No. 4 0-100%

No. 8 0-45%

No. 16 0-15%

No. 50 0-7%

No. 100 0-4%

No. 200 0-2%

4. The aggregate shall be applied at the rate of 20 +/- 3 pounds per square yard. The Contractor shall take all precautions to minimize contamination of the aggregate.

- A sample of the aggregate must be provided to the Town of Adams before project is awarded.

If requested the additional cost for dark(black) granite Project #1 \$ _____ Project #2 _____ Project #3 _____

5. Construction methods

- Equipment: The contractor shall have available and maintain in good working order the equipment and tools necessary to perform the work.

- Surface Preparations: Immediately prior to applying the asphaltic materials, the Contractor shall thoroughly clean the existing surface of all loose material, silt spots, vegetation, and other objectionable material. Dust and other loose material in depressions or other places not reached by mechanical sweepers shall be swept with hand brooms or by blowers or flushers. Particular care shall be taken to thoroughly clean the outer edges of the area to be sealed. All costs associated with preparing existing surfaces as described above shall be included in the bid price for Constrict Chip Seal Surface.

- Applying Asphaltic Materials: A pressure distributor shall be used for applying the asphalt material. It shall have a ground speed control device interconnected with the asphalt emulsion pump such that the specified application rate will be supplied at any speed. The pressure distributor shall be capable of maintaining the asphalt emulsion at the specified temperature. The spray bar nozzles shall produce a uniform fan spray, and the shutoff shall be instantaneous, with no dripping. Each pressure distributor shall be capable of maintaining the specified application rate. Means shall be provided for accurately indicating the temperature of the asphalt material at all times. The thermometer well shall not be in contact with a heating tube. **Application will be with full width equipment capable of applying 24ft. without a center seam.** A hose and spray nozzle attachment shall be provided for applying asphalt material to patches and areas inaccessible to the spray bar. The distributor shall be provided with heaters that can be used to bring the asphalt material to spray application temperature.

- Applying Sealcoat Aggregate: After application of the asphaltic material and when the desired stage of tackiness is attained, aggregate for seal coat cover shall be spread uniformly over the treated surface by approved self-propelled mechanical **full width spreader capable of applying aggregate 24ft.; without a seam.**

- Rolling of Aggregate: Immediately after spreading the aggregate, the surface shall be rolled. Rolling shall start at the edges and continue to the center, lapping one-half the roller width on each successive trip. Rolling shall be accomplished with two pneumatic-tire rollers. The speed and reversing of direction of rollers shall be regulated as to avoid displacement or loosening of the cover material or damage to the asphaltic material. Rolling shall be continued until the aggregate for seal coat cover is thoroughly embedded and the surface is smooth and uniform in texture.

- Sweeping: The contractor will sweep the roads after application, rolling and giving traffic ample time to further embed the material.

- Traffic: The contractor shall proceed in such a manner as to interfere with traffic as little as possible. The Contractor shall provide flagmen to direct traffic away from sweeping operations or on streets where travel will be restricted.

6. Insurance: No contractor shall commence work under this contract until he has obtained all insurance required under this paragraph.

General Liability

\$2,000,000 General Aggregate

\$2,000,000 Products

\$1,000,000 Personal and Advertising

\$1,000,000 Each Occurrence

\$50,000 Fire Damage

\$5,000 Medical Expense

Worker's Compensation and Employer's Liability

\$100,000 each accident

\$500,000 Disease-Policy limit

\$100,000 Disease-each employee

Automobile Liability

\$1,000,000 Combined Single Limit

Property Damage

\$1,000,000 Property Damage

Umbrella Liability

\$2,000,000 Minimum Limit Each Occurrence

\$2,000,000 Aggregate Limit

\$10,000 Maximum Self Retention

6. Performance Bond: The prime contractor shall provide the Town with a payment and performance bond in the amount of contracted price Section 779.14 (1) (s) Wis. Stats. An irrevocable letter of credit may be substituted for payment in lieu of payment and performance bond.

7. Subcontractor: If the contract price exceeds \$30,000 as indexed in Section 779.25 (1) (s) Wis. Stats., the prime contractor agrees, to the extent practicable, to maintain a list of all subcontractors, suppliers and service providers performing, furnish or procuring labor, services, materials, plans, or specification under the contract. (Sec. 779.14 (1e) (b) Wis. Stats.) The Town of Adams may direct payment to subcontractors or may pay the prime contractor with checks that are payable to the prime contractor and to one or more subcontractor Section 779.14 (1m) (d) Wis. Stats.).

8. Liability: The prime contractor shall be solely responsible for all liability associated with the contractor's performance of the project. The prime contractor agrees to indemnify the Town of Adams for any liability that may be imputed to the Town associated with the prime contractor's performance of the project.

9. The Town High crew foreman or the Town Chair shall be notified at least 24 hours before work on the project is started

Other requirements:

By submitting a bid for this project, the prime contractor agrees to do the following:

- a. Pay all claims for labor, service, materials, plans, or specifications performed, furnished, procured, used, or consumed that pertain to the public work Section 779.14 (1e) (a) Wis. Stats.)
- b. Comply with all requirements of any applicable federal and state regulations.
- c. Perform work on the project in a safe, good and workmanlike manner. Comply with any and all applicable federal and state regulations.

9. Methods of payment: The bid price for Constructing Chip Seal Surface shall include all costs associated with furnishing, preparing, hauling, mixing, and applying all materials.

Bar Seal and FA-2 Chip Seal

Location of Site **#1--10th Ave 10ft south of the railroad tracks to the culvert for Duck Creek**

Source of FA-2 Aggregate _____

Gallons of CRS2-P _____ Tons of Chips _____

Total Bid \$ _____

Total with dark(black) granite \$ _____

Location of Site **#2 11th Ave from Dover Dr. south to Duck Creek Dr.**

Source of FA-2 Aggregate _____

Gallons of CRS2-P _____ Tons of Chips _____

Total Bid \$ _____

Total with dark(black) granite \$ _____

Location of Site **#3 9th Ave, from Deerborn Ave. north to County Road "J"**

Source of FA-2 Aggregate _____

Gallons of CRS2-P _____ Tons of Chips _____

Total Bid \$ _____

Total with gray granite \$ _____

The Town of Adams reserves the right to alter the tonnage based on budgetary or other constraints.

The Town reserves the right to reject any and all proposals and to accept the proposal most advantageous to the Town, even if that proposal is not the lowest in cost. All proposals will become the property of the Town of Adams and are subject to Wisconsin Open Records Statutes. Any and all costs incurred in preparing and submitting a response for estimate are the sole responsibility of the submitting firm.